

Universal Drying Rack (JZDRA-156)



CONSTRUCTION/MATERIAL:

- Sturdy construction specifically designed for the demanding corrections environment
- All welded construction
- All fasteners are tamper-proof
- Type 6063-T5 aluminum alloy with wall thickness of 0.070"

WARRANTY/MAINTENANCE:

- Aluminum: 5-year warranty against manufacturing defect

COMPATIBLE INSERTS: JZDRI-5

DIMENSIONS:

Height 72.63" Width 80.50" Depth 22.88"

CAPACITY:

<i>Rack Capacity Per Insert</i>	
<i>Item to Dry</i>	<i>JZDRI-5</i>
Sm & Med Seg Tray Lids	468
Large Seg Tray Lids	312
PPST28/14 Cafeteria Trays	312
PPSTL-28 Lid	312
PPST-1570 Base Tray	312
4" Hotel Pans (12x20x4)	57

COMPONENTS:

Shelving

- Four shelves
- Eight inserts per shelf, 32 inserts per rack
- Interchangeable inserts – mix and match

Casters

- Four 6" poly swivel casters with brakes

INSERTS:

- Inserts made of copolymer material
- Dishwasher safe, temps up to 212° F
- Shatterproof and resists sharpening

JZDRI-5

- 1.813" slots (for cafeteria trays)
- 39 slots per shelf, 156 per rack